

DYNAPAC

Part of the Atlas Copco Group

LP6500 Duplex rollers



Technical data

Dimensions	LP6500 (Manual)	LP6500 (Electrical)
Drum width		650 mm
Width		714 mm
Height		1,045 mm
Length		2,514 m
Masses		
Net mass	658 kg	678 kg
Operating mass (CE)	696 kg	716 kg
Traction		
Theor. gradeability		35
Compaction		
Static linear load	5.35 kg/ cm	5.50 kg/ cm
Speed forward	3.60 km/ h	3.60 km/ h
Speed reverse	2.30 km/ h	2.30 km/ h
Vibration frequency	61 Hz	61 Hz
Nominal amplitude	0.45 mm	0.45 mm
Centrifugal force	21 kN	21 kN
Engine		
Manufacturer		Hatz
Type		1D50S
Fuel		Diesel
Rated power		6.80 kW
Rated power @		2,600 rpm
Rated power (rating standard)		SAE J1995
Fuel consumption / h		1.35 l
Fuel tank capacity		5 l
Hydraulic system		
Driving		Fully hydraulic
Sprinkler system		
Tank capacity		71 l
Type of sprinkling		Gravity

Find your local dealer at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.
The above information is a general description only, all informations are supplied without liability.